

Gantry Hoist and Scaffold Hoist Accessories

Specifications

Lifting Equipment Ltd



Scaffold Hoist Accessories and Gantry Hoist Accessories



Mini Winch-Single Hook Suspension

Capacity	250Kg
Voltage	110v
Motor Type	Single Phase
Height of Lift	20 Metres
Lifting Speed	12 Metres per minute
Extra	IP20 Protection 360 degrees joint saddle hook with s/latch

This mini winch is for indoor user only, can be quickly hooked onto a pole. Supplier with pendant control and 110v plug.



Gin Wheel

Ideal for assisting in manually transporting light loads up a scaffold tower. Self-lubricating wheel, 250mm eyebold suspension point. Supplied with 18mm diameter rope up to 220 metres long.



Wheel Barrow Sling

Wheelbarrow chain, ideal for lifting complete wheelbarrow to varying levels on site. Supplied painted blue. Safe working load 500Kgs with test certificate issued.

300Kg / 500Kg Ballast



Ballast Boxes ideal for ease of counter balancing cantilevered gantry system. Two capacities available 300Kg and 500Kg

80 / 150 Litre Bucket



Ideal for transporting tools and mortar etc. Central lifting point with safety catch to avoid tipping.

Available in 80 Litre - 600W x 480D x 365H
(not including handle) Weight 15Kg

And also 150 Litre - 680W x 600D x 420H
(Not including handle) Weight 25Kg

CALL US FOR MORE INFORMATION

01384 76961