

Plate Clamps

Horizontal Plate Clamp

Lifting Equipment Ltd



Horizontal Plate Clamps





Horizontal plate clamps are designed to be used in pairs with a chain sling or spreader beam arrangement for the lifting and moving of single plates or bundles of plates (minimum plate thickness of 5mm)

A pair of clamps with a double leg chain for smaller plates up to 1500mm long



For larger plates use a spreader beam and two pairs of clamps.



Model	WLL	Jaw capacity	A	B	C	D	E	F	G	Weight
	kg*	mm	mm	mm	mm	mm	mm	mm	mm	kg**
CH1	1000	5 -32	15	82	60	100	32	44	13	8
CH2	2000	5 -32	30	82	60	100	50	73	18	11
CH2L	2000	20 -50	30	82	60	100	50	73	18	12
CH4	4000	5 -50	40	112	80	100	64	92	25	17
CH4L	4000	50 -100	40	112	80	100	64	92	25	23
CH6	6000	5 -75	55	172	100	130	90	130	35	46
CH6L	6000	50 -125	55	172	100	130	90	130	35	56
CH8	8000	5 -75	55	172	105	130	90	130	35	53
CH8L	8000	50 -125	55	172	105	130	90	130	35	60
CH10	10000	5 -100	65	215	120	150	114	130	35	95
CH10L	10000	50 -150	65	215	120	150	114	130	35	108
HH8	8000	5 -50	55	168	105	130	90	114	35	21
HH8L	8000	50 -100	55	168	105	130	90	114	35	28

CALL US FOR MORE INFORMATION
01384 76961