

Hydraulic Lifting

Lightweight Aluminum Jacks

Lifting Equipment Ltd



Lightweight Aluminium Jacks

- Lightweight construction
- Choice of plain ram, toe jack or failsafe (locking ring) design
- Internal safety overload valve
- Safe stop stroke limiting device
- Optional pressure gauge



Model Number	Capacity in Tonnes		Stroke (mm)	Closed Height (mm)	Toe Height (mm)	Base plate L x W (mm)	Weight (kg)
	Head	Toe					
Standard Jack							
LGD620	20	-	152	263	-	178 x 121	10.9
LGD1220	20	-	305	438	-	246 x 121	16.7
LGD630	30	-	152	263	-	197 x 140	15.4
LGD1230	30	-	305	451	-	273 x 140	23.4
LGD660	60	-	152	293	-	251 x 190	27.4
LGD1260	60	-	305	500	-	339 x 190	43.7
Toe Jack							
LGD620C	20	8	152	276	67	246 x 121	14.5
LGD1220C	20	8	305	452	67	246 x 121	22.2
LGD630C	30	12	152	281	73	273 x 140	20.3
LGD1230C	30	12	305	470	73	273 x 140	31.0
LGD660C	60	24	152	327	73	339 x 190	43.1
LGD1260C	60	24	305	533	73	339 x 190	64.9
Failsafe Jack with Locking Ring							
LGD620R	20	-	152	289	-	178 x 121	12.5
LGD1220R	20	-	305	464	-	246 x 121	18.0
LGD630R	30	-	152	292	-	197 x 140	16.5
LGD1230R	30	-	305	479	-	273 x 140	24.5
LGD660R	60	-	152	330	-	251 x 190	30.0
LGD1260R	60	-	305	536	-	339 x 190	44.0

Mutli-Purpose Jacks

- Lightweight aluminium construction
- Operates in any position
- Internal safety overload valve
- Spring assisted return piston
- Choice of 75mm or 125mm stroke length
- Optional base mounting holes



Model Number	Construction Material	Capacity (tonnes)	Stroke (mm)	Closed Height (mm)	Base area L x W (mm)	Weight (kg)
LGD103	Aluminium	10	75	131	162 x 75	4.3
LGD105	Aluminium	10	125	181	162 x 75	5.7

Low Height Jacks

- Multi-positional pump mechanism
- Operates in any position
- Spring assisted return piston
- Lightweight and compact



Model Number	Construction Material	Capacity (tonnes)	Stroke (mm)	Closed Height (mm)	Base area L x W (mm)	Weight (kg)
LGDS10	Steel	10	38	76	212 x 70	4.4
LGD10	Aluminium	10	38	79	212 x 70	3.2
LGD20	Aluminium	20	44	99	233 x 90	5.0

CALL US FOR MORE INFORMATION
01384 76961