

# Roundslings

## Specifications

Lifting Equipment Ltd



## Specifications

1. Colour coded according to DIN-EN 1492-2
2. Capacity stripes; each stripe is equal to 1 tonne capacity
3. The safe working load is clearly and continuously printed on the sleeve
4. Extra strong PU-Impregnated webbing for the sleeve
5. Each sling is packed in plastic with CE declaration of conformity
6. Low elongation
7. Extremely wear-resistant
8. According to Machine Directive 98/37/EC



Safety Colour Code 7:1	Straight Lift	Choke Lift	Basket Lift	Basket Lift	Basket Lift	Multi Leg Slings	Multi Leg Slings
<b>Mode Factor</b>	1.0	0.8	2.0	1.4	1.0	1.4	2.0
<b>Violet</b>	1000	800	2000	1400	1000	1400	2000
<b>Green</b>	2000	1600	4000	2800	2000	2800	4000
<b>Yellow</b>	3000	2400	6000	4200	3000	4200	6000
<b>Grey</b>	4000	3200	8000	5600	4000	5600	8000
<b>Red</b>	5000	4000	10000	7000	5000	7000	10000
<b>Brown</b>	6000	4800	12000	8400	6000	8400	12000
<b>Blue</b>	8000	6400	16000	11200	8000	11200	16000
<b>Orange</b>	10000	8000	20000	14000	10000	14000	20000
<b>Orange</b>	12000	9600	24000	16800	12000	16800	24000

**CALL US FOR MORE INFORMATION**  
**01384 76961**